

Thermodynamics

Heat Expansion

$$\frac{\Delta L}{L} = \alpha \Delta T, \quad \frac{\Delta V}{V} = \beta \Delta T, \quad \beta = 3\alpha$$

Heat

$$Q = mc\Delta T, \quad l_s = \frac{Q_s}{m}, \quad l_a = \frac{Q_a}{m}$$

Fluid Pressure

$$p_{tot} = p_{fluid} + p_{air} = \rho gh + p_{air}$$

Ideal Gas Law

$$pV = NkT \quad \text{or} \quad pV = nRT$$

$$\text{where } n = \frac{m_{tot}}{M} = \frac{N}{N_A} \quad \text{and} \quad R = kN_A$$

Gas Density and Particle Density

$$\rho = \frac{m_{tot}}{V} = \frac{pM}{RT}, \quad n_o = \frac{N}{V} = \frac{p}{kT}$$

Barometric Height Formula

$$p = p_0 e^{-\rho_0 gh/p_0}, \quad h = \frac{p_0}{\rho_0 g} \ln \frac{p_0}{p}$$

Relative Moisture

$$R_M = \frac{p_{\text{water}}}{p_{\text{saturation}}}$$

Van der Waal's Equation

$$\left(p + a \frac{n^2}{V^2} \right) (V - nb) = nRT$$

Critical Point

$$V_k = 3nb, \quad T_k = \frac{8a}{27Rb}, \quad p_k = \frac{a}{27b^2}$$

Molecule Radius

$$r = \left(\frac{3b}{16\pi N_A} \right)^{1/3}$$

Vapor Pressure Curve

$$p = Ae^{-Ml_a/(RT)}$$

Reynolds Number

$$Re = \frac{\rho vd}{\eta}, \quad Re < 2300 \text{ laminar}$$

Volume Flow

$$\Phi = \frac{dV}{dt} = A_1 v_1 = A_2 v_2$$

Bernoullis Equation

$$p_1 + \frac{\rho v_1^2}{2} + \rho gy_1 = p_2 + \frac{\rho v_2^2}{2} + \rho gy_2$$

Poiseuilles Law

$$\Phi = \frac{\pi R^4}{8\eta} \frac{(p_1 - p_2)}{L}$$

Pressure (Microscopic)

$$p = \frac{2}{3} n_o \frac{m_{\text{en}}}{2} \langle v^2 \rangle = \frac{2}{3} n_o \langle W_{\text{kin}} \rangle_{\text{en}}$$

Temperature (Microscopic)

$$\langle W_{\text{kin}} \rangle_{\text{en}} = \frac{3}{2} kT$$

Inner Energy (change)

$$\Delta U = \frac{f}{2} Nk \Delta T = \frac{f}{2} nR \Delta T$$

First Theorem

$$Q = \Delta U + W \quad \text{with} \quad W = \int_1^2 pdV$$

Isokor

$$W \equiv 0$$

Isobar

$$W = p(V_2 - V_1)$$

Isotherm

$$W = nRT \ln\left(\frac{V_2}{V_1}\right)$$

Adiabat

$$W = -\Delta U$$

Molar Heat Capacity

$$C = Mc, \quad C_V = \frac{f}{2}R, \quad C_p = C_V + R$$

Adiabat (Poissons Equations)

$$\begin{aligned} T_1 V_1^{(\gamma-1)} &= T_2 V_2^{(\gamma-1)} \\ p_1 V_1^\gamma &= p_2 V_2^\gamma \end{aligned}$$

Quotient

$$\gamma \equiv \frac{C_p}{C_V} = \frac{c_p}{c_V} = 1 + \frac{2}{f}$$

Circuit Process

$$Q_{\text{net}} = W_{\text{net}} = \oint pdV$$

Efficiency

$$\eta = \frac{W_{\text{net}}}{Q_{\text{in}}} = \frac{Q_{\text{in}} - |Q_{\text{out}}|}{Q_{\text{in}}} = 1 - \frac{|Q_{\text{out}}|}{Q_{\text{in}}}$$

Ideal Efficiency

$$\eta = \frac{T_{\text{warm}} - T_{\text{cold}}}{T_{\text{warm}}} = 1 - \frac{T_{\text{cold}}}{T_{\text{warm}}}$$

Cold Factor (def. and Ideal)

$$K_f \equiv \frac{Q_{\text{in}}}{|W_{\text{net}}|}, \quad K_f = \frac{T_{\text{cold}}}{T_{\text{warm}} - T_{\text{cold}}}$$

Heat Factor (def. and Ideal)

$$V_f \equiv \frac{Q_{\text{out}}}{|W_{\text{net}}|}, \quad V_f = \frac{T_{\text{warm}}}{T_{\text{warm}} - T_{\text{cold}}}$$

Gauss Distribution

$$f(v_z) = \sqrt{\frac{m_{\text{en}}}{2\pi kT}} e^{-m_{\text{en}}v_z^2/(2kT)}$$

Maxwell–Boltzmann Distribution

$$f(v) = 4\pi v^2 \left(\frac{m_{\text{en}}}{2\pi kT}\right)^{3/2} e^{-m_{\text{en}}v^2/(2kT)}$$

Averages

$$\begin{aligned} \langle v \rangle &= \sqrt{\frac{8kT}{\pi m_{\text{en}}}}, \quad \langle v \rangle = 2\langle |v_x|\rangle \\ \langle W_{\text{kin}} \rangle &= \left\langle \frac{m_{\text{en}}v^2}{2} \right\rangle = \frac{m_{\text{en}}}{2}\langle v^2 \rangle = \frac{3}{2}kT \end{aligned}$$

Collision Number (per second and square meter)

$$n^* = \frac{n_o}{4}\langle v \rangle$$

Mean Free Path

$$l = \frac{1}{n_o \pi d^2 \sqrt{2}}$$

Heat Conduction (General and Rod)

$$P = -\lambda A \frac{dT}{dx}, \quad P = \lambda A \frac{T_1 - T_2}{L}$$

Heat Transfer

$$P = \alpha A \Delta T$$

Radiation

$$P_{\text{ideal}} = \sigma AT^4, \quad P_{\text{real}} = eP_{\text{ideal}}$$