

## Diffraction and Interference

### Intensity when Diffraction

$$I = I_0 \left( \frac{\sin \beta}{\beta} \right)^2 \quad \text{with} \quad \beta = \frac{\pi b \sin \theta}{\lambda}$$

### Diffraction minimum of slit

$$b \sin \theta = m\lambda \quad \text{where} \quad m = \pm 1, \pm 2, \pm 3, \dots$$

### Diffraction minimum of round opening

$$D \sin \theta = k\lambda$$

$$\text{where } k = 1, 22, 2, 23, 3, 24, 4, 25, 5, 25\dots$$

### Rayleigh's Resolution Criterion

Central top for the first point over the first min for the second point

### Interference if Diffraction is neglected

$$I = I_0 \left( \frac{\sin N\gamma}{\sin \gamma} \right) \quad \text{där} \quad \gamma = \frac{\pi d \sin \theta}{\lambda}$$

### Interference gives main max if

$$d \sin \theta = m\lambda \quad \text{där} \quad m = \pm 1, \pm 2, \pm 3, \dots$$

### Visibility

$$V = \frac{I_{max} - I_{min}}{I_{max} + I_{min}}$$

### Grating, transmission or reflection

$$d(\sin \alpha_2 + \sin \alpha_1) = m\lambda$$

$$d(\sin \alpha_2 - \sin \alpha_1) = m\lambda$$

### Max or min in case of interference in thin layers

$$2n_2 d \cos \alpha_2 = m\lambda \quad \text{där} \quad m = 0, \pm 1, \pm 2, \dots$$

### Finesse in Fabry-Perot interferometer

$$F = \frac{\Delta f}{\delta f} \quad \text{where} \quad \Delta f = \frac{c}{2d}$$

### Airy Function

$$T = \frac{1}{1 + \left[ \frac{4r^2}{(1-r^2)^2} \right] \sin^2 \left( \frac{\delta}{2} \right)}$$